

12

ADA114644

**A COMPARISON OF THE LONGLEY-RICE SEMI-EMPIRICAL MODEL
WITH THEORETICAL MODELS FOR COHERENT SCATTER**

By

M. M. WEINER

MAY 1982

Prepared for

**DEPUTY FOR TACTICAL SYSTEMS
ELECTRONIC SYSTEMS DIVISION
AIR FORCE SYSTEMS COMMAND
UNITED STATES AIR FORCE
Hanscom Air Force Base, Massachusetts**



**DTIC
ELECTE
MAY 20 1982**
S D D

Project No. 6480

Prepared by

**THE MITRE CORPORATION
Bedford, Massachusetts**

Contract No. F19628-81-C-0001

Approved for public release;
distribution unlimited.

DTIC FILE COPY

82 05 20 026

When U.S. Government drawings, specifications, or other data are used for any purpose other than a definitely related government procurement operation, the government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise, as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Do not return this copy. Retain or destroy.

REVIEW AND APPROVAL

This technical report has been reviewed and is approved for publication

FOR THE COMMANDER

Richard L. Hocker

(Signature)

RICHARD L. HOCKER, Major, USAF
AF SINGARS Program Manager
SINK TALK System Program Office

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER ESD-TR-82-133	2. GOVT ACCESSION NO. AD-A114644	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) A COMPARISON OF THE LONGLEY-RICE SEMI-EMPIRICAL MODEL WITH THEORETICAL MODELS FOR COHERENT SCATTER		5. TYPE OF REPORT & PERIOD COVERED
7. AUTHOR(s) M. M. WEINER		6. PERFORMING ORG. REPORT NUMBER M81-27
9. PERFORMING ORGANIZATION NAME AND ADDRESS The MITRE Corporation P. O. Box 208, Bedford, MA 01730		8. CONTRACT OR GRANT NUMBER(s) F19628-81-C-0001
11. CONTROLLING OFFICE NAME AND ADDRESS Deputy for Tactical Systems Electronic Systems Division, AFSC Hanscom Air Force Base, MA 01731		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Project No. 6480
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE May 1982
		13. NUMBER OF PAGES 8
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) BACK SCATTER MULTI-PATH TERRAIN SURFACE BI-STATIC SCATTER RADIO PROPAGATION CLUTTER ROUGH SURFACE SCATTERING COHERENT SCATTER SEA SURFACE LONGLEY-RICE SURFACE TRUTH		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The Longley-Rice semi-empirical propagation model is compared with theoretical models for coherent scatter of microwaves from moderately rough surfaces. ↑		

DD FORM 1473 EDITION OF 1 NOV 81 IS OBSOLETE

UNCLASSIFIED
SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

Accession For	
DTIC GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	



The effect of terrain and sea roughness on coherent scatter of microwaves for a line-of-sight, multipath mode of propagation in the specular direction is given by the Longley-Rice prediction model as ¹

$$\langle \rho \rangle = \exp(-g^{1/2}/2) \quad (1)$$

where

$\langle \rho \rangle$ = expectation of the surface roughness field amplitude reflection coefficient

$g^{1/2}$ = surface roughness Rayleigh parameter

$$= (2\pi/\lambda) (2 \sin \psi_i) \sigma_H$$

λ = wavelength of incident radiation

ψ_i = grazing angle of incidence on mean surface level (MSL)

σ_H = standard deviation of the surface height random variable H with respect to the MSL.

This model differs from theoretical models which assume particular probability density functions for the height random variable. In particular, this model differs from theoretical models which assume that the height random variable is exponentially distributed², normally distributed^{3,4}, or pseudo-exponentially distributed⁵. The amplitude reflection coefficient $\langle \rho \rangle$ for these theoretical models are given by²

$$\langle \rho \rangle = \begin{cases} \exp(-g/2) & \text{normally distributed} & (2a) \\ (1 + \frac{2}{3}g)^{-3/4} & \text{pseudo-exponentially distributed} & (2b) \\ (1 + \frac{g}{2})^{-1} & \text{exponentially distributed} & (2c) \end{cases}$$

Eq. (1) is a semi-empirical formula which has no theoretical basis but which was employed by Longley-Rice to fit empirical data^{6,7}. The semi-empirical model of Longley-Rice and the theoretical models of Eq. (2) are compared with empirical data in Figs. 1-3 for microwave scatter from the ocean, microwave scatter from terrain and sea surfaces, and acoustical scatter from an artificial surface submerged in a water tank, respectively. It will be noted that the exponentially distributed model and the semi-empirical model give good agreement with data for both moderately rough and smooth surfaces. However, the semi-empirical model does not have zero slope at $g^{1/2} = 0$ as does the theoretical models and as does most of the empirical data.

In conclusion, the Longley-Rice semi-empirical model does not appear to offer any better fit to the empirical data than does the exponentially distributed model. The exponentially distributed model has the distinct advantages of having a theoretical basis and of offering an interesting physical interpretation of the stochastic process associated with the surface profile.²




FIGURE 1.

COHERENT AMPLITUDE REFLECTION COEFFICIENT.
COMPARISON OF MODELS WITH EXPERIMENTAL
DATA FOR MICROWAVE SCATTER FROM THE OCEAN.




FIGURE 2. COHERENT POWER REFLECTION COEFFICIENT. COMPARISON OF MODELS WITH DATA FOR MICROWAVE SCATTER FROM TERRAIN AND SEA SURFACES.




FIGURE 3. COHERENT POWER REFLECTION COEFFICIENT. COMPARISON OF MODELS WITH EXPERIMENTAL DATA FOR SCATTER OF ACOUSTICAL WAVES FROM A SURFACE MODEL SUBMERGED IN A WATER TANK.

REFERENCES

1. A. G. Longley, and P. L. Rice, "Prediction of Tropospheric Radio Transmission Loss Over Irregular Terrain, A Computer Method - 1968", U.S. National Bureau of Standards, ESSA Tech. Report ERL 79-ITS 67, 1968, p. 3-3, Eq. (3.5), NTIS, AD 676 874.
2. M. M. Weiner and G. A. Robertshaw, "Coherent Scatter of Microwaves from Moderately Rough Surfaces," ESD-TR-81-147, The MITRE Corporation, Bedford, Mass., August 27, 1981, NTIS, AD A106 133.
3. P. Beckmann and A. Spizzichino, "The Scattering of Electromagnetic Waves from Rough Surfaces" (Pergamon Press, Oxford, 1963) pp. 246-247.
4. C. I. Beard, "Coherent and Incoherent Scattering of Microwaves from the Ocean, IRE Transactions on Antennas and Propagation, Vol. AP-9, pp. 470-483 (September 1961).
5. M. L. Boyd and R. L. Deavenport, "Forward and Specular Scattering from a rough surface; Theory and Experiment", J. Acoust. Soc. of America, Vol. 53, pp. 791-801 (March, 1971).
6. Telephone conversation with P. L. Rice on February 19, 1981.
7. M. M. Weiner, "Terrain and Sea Surface Truth: Profile Distributions", ESD-TR-81-387 (The MITRE Corporation, Bedford, MA, December 1981), NTIS, AD A110 219.